

PERSONSLUSER EMD

High security booths:

One person at the time control system

Sizes: EMD K 1050 x 1050 x 2360mm

EMD K Plus 1150 x 1150 x 2360mm

EMD K Maxi 1500 x 1500 x 2360mm

Free passage width: 580 x 2000mm

700 x 2000mm

900 x 2000mm



- > weight: from 650 Kg to 900 Kg according to the version and to options requested
- > power supply: 220V, 50/60Hz
- > power consumption: 75W
- > voltage: 12-24VDC
- > **throughput:** 4-5/1' one-way; 7-8/1' two-ways according to the model
- > battery back-up: provides up to 1000 cycles (12V – 18Ah)
- > casing 3 mm steel
- > paint finishes: colours within the standard RAL range (others available on request)
- > **sliding doors and side panels: laminated glass 27/28 mm.** UNI EN 1063 class BR3/S (19/20 mm class BR2/S EM24K Maxi model) – UNI EN 356 class P6B. Different laminated glass available on request
- > **side panels: painted steel** (on request)
- > doors motors: 24VDC (reversible or mixed option for free doors opening on power failure)
- > spot-lights: 12V – 50/60Hz
- > programmable micro-processor electronics
- > electronically self-adjusted braking, speed control and accident prevention devices
- > **booth floor: 25mm thick**